


This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H. wei	19/03/17	19/03/17



1 Electrical 电气性能

- 1.1 Impedance 特性阻抗: 50 Ω
- 1.2 Frequency 频率范围: DC~11GHz
- 1.3 VSWR 电压驻波比: $\leq 1.30 @ 6\text{GHz}$
- 1.4 Insertion Loss (dB): $\leq 0.05 \times \text{Sqrt. (f_GHz)}$
- 1.5 Insulation resistance 绝缘电阻: $\geq 5000\text{M}\Omega$
- 1.6 Dielectric withstanding voltage 介质耐压: 1000V

2 Environmental & Mechanical 环境 & 机械性能

- 2.1 Temperature range 温度范围: $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$
- 2.2 RoHS Compliant 符合RoHS
- 2.3 Durability 寿命: >500 cycles (次)

3 Materials & Finish 材料 & 涂镀

- 3.1 Body 外壳: Brass, Gold Plated 黄铜, 镀金
- 3.2 Insulator 绝缘介质: Teflon 聚四氟乙烯
- 3.3 Contact Pin 中心导体: Brass, Gold Plated 黄铜, 镀金
- 3.4 Crimp Ferrule 线夹: Copper Nickel Plated 黄铜, 镀镍

Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17	TITLE: RF Coaxial Connector RPSMA female conn. for LMR300 cable	 成都恒利泰科技有限公司 Chengdu HenryTech Technology co., Ltd			
ENGINEER: L.yu 19/03/17					
APPROVED: W.yi 19/03/17		 DIMENSION IN MILLIMETERS (mm)			
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .X ±0.20 .XX ±0.10 ANGLES ±1°		PART NO: HL-RPSMA-J300Y	SIZE: A4	SCALE: N/A	SHEET: 1/1