


This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H.wei	19/03/17	19/03/17



1 Electrical

1.1 Impedance	50 Ω
1.2 Frequency	DC ~18GHz
1.2 Dielectric withstanding voltage	1000V(volts RMS)
1.3 Center contact resistance	$\leq 3\text{m}\Omega$
1.4 Outer contact resistance	$\leq 2\text{m}\Omega$
1.5 Insulation resistance:	$\geq 5000\text{M}\Omega$
1.6 VSWR	1.25 : 1

2 Environmental&Mechanical

2.1 Temperature range	-45 $^{\circ}$ C ~85 $^{\circ}$ C
2.2 RoHs Compliant	
2.3 Durability	≥ 500 cycles

3 Materials&plating

3.1 Body:	Brass, Nickel plated
3.2 Insulator:	Teflon
3.3 Contact Pin:	Beryllium-copper, Gold plated

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17
ENGINEER: L.yu 19/03/17
APPROVED: W.yi 19/03/17
TOLERANCES UNLESS OTHERWISE SPECIFIED: X ± 0.50 .X ± 0.20 .XX ± 0.10 ANGLES $\pm 1^{\circ}$

TITLE:
RF Coaxial Connector
RF Connector SMA
Female Flange Conn.
Terminal

PART NO: HL-SMA-KFD1084

 成都恒利泰科技有限公司
Chengdu HenryTech Technology co., Ltd

 DIMENSION IN MILLIMETERS (mm)

SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A
----------	------------	------------	--------