




This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release		H.wei	19/03/17	19/03/17



Recommended
Mounting Hole



1 Electrical 电气性能

- 1.1 Impedance 特性阻抗: 50 Ω
- 1.2 Frequency 频率范围: DC~18GHz
- 1.3 VSWR 电压驻波比: ≤ 1.20 @ 6GHz
- 1.4 Insulation resistance 绝缘电阻: $\geq 5000 M\Omega$
- 1.5 Dielectric withstanding voltage 介质耐压: 1000V
- 1.6 Center contact 中心导体接触电阻 $\leq 3.0 m\Omega$
- 1.7 Outer contact 外导体接触电阻 $\leq 2.0 m\Omega$

2 Environmental & Mechanical 环境 & 机械性能


- 2.1 Temperature range 温度范围: -55 $^{\circ}$ C ~ +125 $^{\circ}$ C
- 2.2 RoHS Compliant 符合 RoHS
- 2.3 Durability 寿命: >500 cycles (次)

3 Materials & Finish 材料 & 涂镀

- 3.1 Body 外壳: Brass, Gold plated 黄铜, 镀金
- 3.2 Insulator 绝缘介质: Teflon 聚四氟乙烯
- 3.3 Contact Pin 中心导体: Beryllium-Copper, Gold plated 铍青铜, 镀金

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17	TITLE: RF Coaxial Connector RF Connector SMA Female Flange Conn. Terminal	 成都恒利泰科技有限公司 Chengdu HenryTech Technology co., Ltd			
ENGINEER: L.yu 19/03/17					
APPROVED: W.yi 19/03/17		 DIMENSION IN MILLIMETERS (mm)			
TOLERANCES UNLESS OTHERWISE SPECIFIED: X ± 0.50 .X ± 0.20 .XX ± 0.10 ANGLES $\pm 1^{\circ}$	PART NO: HL-SMA-KFD267	SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A