

This document contains proprietary information and such informationmay not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	———	H.wei	12/7/06	12/7/06





技术特性/Electrical Specifications

特性阻抗/Impedance	50Ω
频率范围/Frepuency Range	DC-18GHz
电压驻波比/VSWR	≤1.25
插入损耗/Insert Loss	≤0.06xsqt.(f GHz)dB
耐　压/Withstanding Voitage	≥750V
绝缘电阻/Insulation Resistance	≥5000MΩ

连接参数/The connection parameters

耐久性/durability	≥500次 (cycles)

环境参数/Environmental Data

温度范围/Temperature Range	-55℃ to 155℃

材料/Material Data

外导体/Outer contact	黄铜 Brass/金 Gold Plated
中心导体/Center contact	磷青铜/Phosphor Bronze/金 Gold Plated
绝缘介质/Insulator	聚四氟乙烯/PTFE

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 12/07/06	TITLE: RF Coaxial Connector SMA Female Flange Conn. Terminal	HenryTech
ENGINEER: L.yu 12/07/06		
APPROVED: W.yi 12/07/06		DIMENSION IN MILLIMETERS (mm)
TOLERANCES UNLESS OTHERWISE SPEFICIED X ±0.50 .X ±0.20 .XX ±0.10 ANGLES ±1°	PART NO: HL3-SMA-KFD4-4-2	SIZE: A4 / SCALE: N/A / SHEET: 1/1 / REV: A