
LTCC Bandpass Filter 低温共烧陶瓷 带通滤波器

产品型号（Product model）：HM-BP2520-5800-125M-1

一、电气性能 Electrical Specifications（TAMB=25°C）

No.	项目		指标
1	中心频点 Center Frequency		5800MHz
2	通带频率 Passband Frequency		5725-5850MHz
3	阻抗 Impedance		50Ω
4	插损 Insertion Loss	5725~5850MHz	≤2.3dB
5	纹波 Ripple	5725~5850MHz	≤1dB
6	驻波比 VSWR	5725~5850MHz	≤2.0
7	带外抑制 OOBR	902~998MHz	≥50dB
		3919~4044MHz	≥30dB
		4822~4947MHz	≥30dB
8	工作温度 Operating Temperature		-40℃ ~ +85℃
9	存储温度 Storage Temperature		-40℃ ~ +85℃
10	最大输入功率 Input Power		1W

二、外形尺寸 Outline Drawing（Unit：mm）




L	2.50 ± 0.20
W	2.00 ± 0.20
T	1.00 ± 0.20
A	0.50 ± 0.10
B	0.20 ± 0.10

三、引脚定义 Pin Connections

输入 input Port	1
输出 output Port	2
接地 GND	3、4

四、焊盘尺寸 PCB Land Pattern




注意 Note：

1. 单位 Unit: mm
2. 线宽应设计为匹配 50Ω特性阻抗，具体取决于 PCB 材料和厚度。
Line width to be designed to match 50 Ω characteristic impedance, depending on PCB material and thickness


Tel:+86-28-85589664
E-mail:428858430@qq.com
Web:www.hltchips.com
Room 1401, 14th Floor, Building 5, Hua xi Science and Technology Innovation Center, No.50, Shuxi Road, Jinniu District, Chengdu City

LTCC Bandpass Filter 低温共烧陶瓷 带通滤波器

五、测试曲线 Test Curve @ 25℃



六、回流焊温度 Reflow Soldering Temperature



Tel:+86-28-85589664
E-mail:428858430@qq.com
Web:www.hltchips.com
Room 1401, 14th Floor, Building 5, Hua xi Science and Technology Innovation Center, No.50, Shuxi Road, Jinniu District, Chengdu City