
LTCC Bandpass Filter 低温共烧陶瓷带通滤波器

产品型号（Product model）：HM-BP6025-6025-350M

一、电气性能 Electrical Specifications（TAMB=25°C）

No.	项目		指标
1	中心频点 Center Frequency		6025MHz
2	通带频率 Passband Frequency		5850-6200MHz
3	阻抗 Impedance		50Ω
4	插损 Insertion Loss	5850~6200MHz	≤3.0dB
5	驻波比 VSWR(In BW)		≤2.5
6	带外抑制 OOBR	2000~5300MHz	≥35dB
		6700~10000MHz	≥20dB
7	工作温度 Operating Temperature		-40℃ ~ +85℃
8	存储温度 Storage Temperature		-40℃ ~ +85℃
9	最大输入功率 Input Power max		5W


二、外形尺寸 Outline Drawing（Unit：mm）



L	6.00±0.20
W	2.50±0.20
T	2.00MAX
A	0.60±0.10
B	0.40±0.10
C	0.40±0.10

三、引脚定义 Pin Connections

输入 input Port	1
输出 output Port	2
接地 GND	3、4



四、焊盘尺寸 PCB Land Pattern


注意 Note：

1. 单位 Unit: mm
2. 线宽应设计为匹配 50Ω 特性阻抗，具体取决于 PCB 材料和厚度。
Line width to be designed to match 50 Ω characteristic impedance, depending on PCB material and thickness


Tel:+86-28-85589664
E-mail:428858430@qq.com
Web:www.hltchips.com
Room 1401, 14th Floor, Building 5, Huaxi Science and Technology Innovation Center, No.50, Shuxi Road, Jinniu District, Chengdu City

LTCC Bandpass Filter 低温共烧陶瓷带通滤波器

五、测试曲线 Test Curve @ 25℃



六、回流焊温度 Reflow Soldering Temperature



Tel:+86-28-85589664
E-mail:428858430@qq.com
Web:www.hltchips.com
Room 1401, 14th Floor, Building 5, Huaxi Science and Technology Innovation Center, No.50, Shuxi Road, Jinniu District, Chengdu City