
10-20000Mhz 50Ω 1:2Ratio Transformer

HT-BAL-0020SLG

Mechanical Dimensions:



Notes:


1: Dimensions in mm.

2: Tolerance ±0.3mm unless otherwise noted.

Ports Configuration:

In	1
Out 1 (0°)	2
Out 2(180°)	3
Ground	Other

Schematic:



Maximum Ratings:

Parameters	Conditions	Unit	Min	Max
RF Power		Watt		1
DC Current		mA		300
Operating Temperature Range		Degree Cel	-55	100
Storage Temperature Range		Degree Cel	-65	125
Moisture Sensitivity Level				1

Ordering Information:

Part Description	Details
HT-BAL-0020SLG	500 per reel

Tel: +86-28-85589664
E-mail: mr_li@henglitaitech.com
Web: www.hltchips.com
Room 1401, 14th Floor, Building 5, Huaxi Science and Technology Innovation Center, No. 50, Shuxi Road, Jinniu District, Chengdu City

10-20000Mhz 50Ω 1:2Ratio Transformer HT-BAL-0020SLG


Electrical Specifications: Zo=50 Ohm Pin = 0 dBm

Parameter	Test Conditions	Unit	Min	Typical	Max
Frequency Range	-	MHz	10	~	20000
Nominal Insertion Loss	10-20000MHz	dB	-	3	-
Insertion Loss	10-20000MHz	dB	-	-	8
INPUT VSWR	10-20000MHz	-	-	1.5	-
OUTPUT VSWR	10-20000MHz	-	-	1.6	-
Isolation	10-20000MHz	dB	8	12	-
Common Mode Rejection	10-20000MHz	dB	22	35	-
Phase Balance	10-20000MHz	Degree	-	±5	±10
Amplitude Balance	10-20000MHz	dB	-	±0.4	±1.2

Notes:

1: Specifications guaranteed over the operating temperature range.

Typical Performance Curves:



Tel: +86-28-85589664
E-mail: mr_li@henglitaitech.com
Web: www.hltchips.com
Room 1401, 14th Floor, Building 5, Huaxi Science and Technology Innovation Center, No. 50, Shuxi Road, Jinniu District, Chengdu City